


Description

The DFI75HF17DERE1 offer lower losses and higher energy for soft switching applications.



Features

- 1700V/75A, $V_{CE(sat)}(typ.) = 1.47V$
- Lower losses and higher energy
- Excellent short-circuit capability
- 34mm half bridge module

Applications

- Motor drive
- Inverter
- Power supply
- Wind Turbines

Circuit diagram




Figure 1. Out drawing & circuit diagram for DFI75HF17DERE1

Pin Configuration and Marking Information




Figure 2. Pin configuration

Module

Parameter	Conditions	Value	Unit
Isolation Voltage	RMS, f = 50Hz, t =1min	2.5	kV
Material of module baseplate	-	Cu	-
Creepage distance	terminal to heatsink terminal to terminal	26 21	mm
Clearance	terminal to heatsink terminal to terminal	23.6 10	mm
CTI	-	>200	-
Module lead resistance, terminals – chip	T _C =25°C	0.8	mΩ
Mounting torque for module mounting	M5, M6	3 to 6	Nm
Weight	-	160	g

Maximum Ratings (IGBT, $T_j = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Conditions	Ratings	Unit
V_{CES}	Collector-Emitter Voltage	G-E Short	1800	V
V_{GES}	Gate-Emitter Voltage	C-E Short	± 30	V
I_C	DC Continuous Collector Current	$T_C = 100^\circ\text{C}$	75	A
I_{CM}	Pulse Collector Current	$t_p = 1\text{ms}$, Note1	150	A
P_C	Maximum Power Dissipation	$T_C = 25^\circ\text{C}$, $T_j = 175^\circ\text{C}$ (IGBT)	525	W
T_j	junction temperature	-	-40 to 175	$^\circ\text{C}$
T_{stg}	Storage temperature	-	-40 to 125	$^\circ\text{C}$

Note1: Pulse width limited by maximum junction temperature

Maximum Ratings (Freewheeling diode, $T_j = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Conditions	Ratings	Unit
V_{RRM}	Peak Repetitive Revers Voltage	-	1700	V
I_F	Diode forward Current	-	75	A
I_{FRM}	Repetitive peak forward Current	$t_p = 1\text{ms}$, Note1	150	A
T_j	junction temperature	-	-40 to 175	$^\circ\text{C}$
T_{stg}	Storage temperature	-	-40 to 125	$^\circ\text{C}$

Note1: Pulse width limited by maximum junction temperature

IGBT Electrical characteristics (T_j=25°C unless otherwise specified, chip)

Symbol	Item	Condition		Value			Unit
				Min.	Typ.	Max.	
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C =75A, V _{GE} =15V	T _j =25°C	-	1.47	1.77	V
			T _j =150°C	-	1.55	-	V
			T _j =175°C	-	1.59	-	V
V _{GE(th)}	Gate-Emitter threshold Voltage	I _C =1mA, V _{CE} =V _{GE}		5.0	5.8	6.5	V
Q _G	Gate charge	V _{GE} = -15V to +15V		-	0.993	-	μC
R _{Gint}	Internal gate resistor	-	T _j =25°C	-	9.0	-	Ω
C _{ies}	Input Capacitance	V _{CE} =25V	T _j =25°C	-	8950	-	pF
C _{oes}	Output Capacitance	V _{GE} =0V		-	342	-	pF
C _{res}	Reverse transfer Capacitance	f=1MHz		-	129	-	pF
I _{CES}	Collector- Emitter Cut off Current	V _{CE} =1800V, V _{GE} =0V	T _j =25°C	-	-	1	mA
I _{GES}	Gate-Emitter Leakage Current	V _{GE} =±30V, V _{CE} =0V	T _j =25°C	-	-	300	nA
t _{d(on)}	Turn-on delay time	V _{CC} =900V I _C =75A R _G =5.0Ω V _{GE} =+15V/-8V Inductive Load	T _j =25°C	-	136	-	ns
			T _j =150°C	-	163	-	
t _r	Rise time		T _j =25°C	-	41	-	ns
			T _j =150°C	-	35	-	
t _{d(off)}	Turn-off delay time		T _j =25°C	-	272	-	ns
			T _j =150°C	-	314	-	
t _f	Fall time		T _j =25°C	-	331	-	ns
			T _j =150°C	-	504	-	
E _{on}	Turn-on power dissipation		T _j =25°C	-	11.1	-	mJ
			T _j =150°C	-	15.4	-	
E _{off}	Turn-off power dissipation		T _j =25°C	-	15.2	-	mJ
			T _j =150°C	-	23.7	-	
R _{th(j-c)}	Thermal Resistance, Junction to Case (IGBT) , Note1			-	-	0.25	°C/W

Note1: Assumes Thermal Conductivity of grease is 2.8 W/m · K and thickness is 50μm.

Freewheeling Diode Electrical characteristics ($T_j=25^\circ\text{C}$ unless otherwise specified, chip)

Symbol	Item	Condition		Value			Unit
				Min.	Typ.	Max.	
V _F	Diode Forward Voltage	I _F =75A, V _{GE} =0V	T _J =25°C	-	1.62	-	V
			T _J =150°C	-	1.59	-	V
			T _J =175°C	-	1.55	-	V
t _{rr}	Diode Reverse Recovery Time	V _R =900V V _{GE} =-8V I _F =75A di/dt =267A/μs	T _J =25°C		65		ns
			T _J =150°C		191		ns
I _{rr}	Peak reverse recovery Current		T _J =25°C	-	52	-	A
			T _J =150°C	-	65	-	A
Q _{rr}	Recovered charge		T _J =25°C	-	3.75	-	μC
			T _J =150°C	-	9.1	-	μC
E _{rr}	Reverse recovered energy		T _J =25°C	-	2.0	-	mJ
			T _J =150°C	-	5.0	-	mJ
R _{th(j-c)}	Thermal Resistance, Junction to Case (Diode), Note1			-	-	0.40	°C/W

Note1: Assumes Thermal Conductivity of grease is $2.8\text{ W/m} \cdot \text{K}$ and thickness is $50\mu\text{m}$.

Test Conditions




Figure 3. Switching time measure circuit






Figure 4. Switching time definition






Figure 7. I_c vs V_{GE}
 $V_{CE} = 20\text{V}$




Figure 8. I_F vs V_F




Figure 9. E_{on} , E_{off} , E_{RR} vs I_c (Typ)
 $V_{CC} = 900\text{V}$, $V_{GE} = +15\text{V}/-8\text{V}$, $R_g = 5.0\Omega$, $T_j = 25^\circ\text{C}$
Inductive Load




Figure 10. E_{on} , E_{off} , E_{RR} vs I_c (Typ)
 $V_{CC} = 900\text{V}$, $V_{GE} = +15\text{V}/-8\text{V}$, $R_g = 5.0\Omega$, $T_j = 150^\circ\text{C}$
Inductive Load




Figure 11. E_{on} , E_{off} vs R_G (Typ)
 $V_{CC}=900V$, $V_{GE}=+15V/-8V$, $I_C=75A$, $T_j=25^\circ C$
 Inductive Load




Figure 12. E_{on} , E_{off} vs R_G (Typ)
 $V_{CC}=900V$, $V_{GE}=+15V/-8V$, $I_C=75A$, $T_j=150^\circ C$
 Inductive Load




Figure 13. Gate charge




Figure 14. C_{ies} , C_{oes} , C_{res} vs V_{CE}
 $T_j=25^\circ C$, $f=1MHz$

IMPORTANT NOTICE:

This product data sheet describes the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively under the terms and conditions of the supply agreement. There will be no guarantee or of any kind for the product and its characteristics.

The data contained in this document is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the product's suitability for the intended application and the completeness of the product data concerning such application.

Due to technical requirements, our product may contain dangerous substances. For information on the types in question, please contact the sales staff responsible for you.

Changes to this product data sheet are reserved.

Please contact the sales staff (Sales@leapers-power.com) for further information on the product, technology, delivery terms, conditions and prices.