

Description

The DFS400CU17I3C2 is a Chopper SiC MOSFET Power Module. It integrates high performance SiC MOSFET chips designed for the applications such as xEV Application and Renewable energy.



Features

- Blocking voltage 1700V
- $R_{DS(on)} = 5.2m\Omega$ ($V_{GS} = 15V$)
- Low thermal resistance with Si₃N₄ AMB
- 175°C maximum junction temperature
- Low Inductive Design
- Thermistor inside
- Pressfit terminal
- Copper base size: 79mm*62mm

Applications

- xEV Applications
- Converter
- Vehicle Fast Chargers
- Renewable energy

Circuit diagram




Figure 1. Out drawing & circuit diagram for DFS400CU17I3C2

Pin Configuration and Marking Information




Figure 2. Pin configuration

Module

Parameter	Conditions	Value	Unit
Isolation Voltage	RMS, f =50Hz, t =1min	4	KV
Material of module baseplate	-	Cu	-
Creepage distance	terminal to heatsink terminal to terminal	14.5 10	mm
Clearance	terminal to heatsink terminal to terminal	12.5 10	mm
CTI	-	600	-
Module lead resistance, terminals–chip	T _c =25°C	0.5	mΩ
Mounting torque for module mounting	M5, M6	3 to 6	Nm
Weight	-	250	g

Maximum Ratings (T_j = 25°C unless otherwise specified)

Symbol	Parameter	Conditions	Ratings	Unit
V _{DSS}	Drain-Source Voltage	G-S Short	1700	V
V _{GSS}	Gate-Source Voltage (+)	D-S Short	20	V
V _{GSS}	Gate-Source Voltage (-)	D-S Short	-10	V
V _{GSSSurge}	G-S Voltage (t _{surge} < 300nsec)	D-S Short, Note1	-10 to 20	V
I _{DS}	DC Continuous Drain Current	T _f = 25°C, V _{GS} = 15V	420	A
I _{DS}	DC Continuous Drain Current	T _f = 65°C, V _{GS} = 15V	360	A
I _{DSM}	Pulse Forward Current	T _f = 25°C, Pulse width = 1ms, V _{GS} = 15V, Note2	800	A
I _F	Forward Current (Diode)	T _f = 65°C	430	A
I _{FRM}	Pulse Forward Current (Diode)	Less than 1ms, Note2	800	A
I ² t	∫I ² dt	T _p = 10ms, T _C = 25°C	11248	A ² S
P _{tot}	Total Power Dissipation	T _C = 25°C	2585	W
T _{jmax}	Max Junction Temperature	-	175	°C
T _{stg}	Storage Temperature	-	-40 to 125	°C

Note1: Recommended Operating Value, -4V/+15V, -5V/+15V

Note2: Pulse width limited by maximum junction temperature

NTC characteristics

Symbol	Parameter	Condition	Value			Unit
			Min.	Typ.	Max.	
R ₂₅	Resistance	T _C = 25°C	-	5	-	kΩ
ΔR/R	Deviation of R ₁₀₀	T _C = 100°C, R ₁₀₀ = 493Ω	5	-	5	%
P ₂₅	Power dissipation	T _C = 25°C	-	-	20	mW
B _{25/50}	B-value	R ₂ = R ₂₅ exp [B _{25/50} (1/T ₂ - 1/(298,15 K))]	-	3375	-	K
B _{25/80}	B-value	R ₂ = R ₂₅ exp [B _{25/80} (1/T ₂ - 1/(298,15 K))]	-	3411	-	K
B _{25/100}	B-value	R ₂ = R ₂₅ exp [B _{25/100} (1/T ₂ - 1/(298,15 K))]	-	3433	-	K

MOSFET Electrical characteristics (T_j=25°C unless otherwise specified, chip)

Symbol	Item	Condition	Value			Unit	
			Min.	Typ.	Max		
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =160uA	1700	-	-	V	
I _{DSS}	Zero gate voltage drain Current	V _{DS} =1700V, V _{GS} =0V	-	4	160	μA	
V _{GS(th)}	Gate-source threshold Voltage	I _D =240mA V _{DS} =V _{GS}	T _j =25°C	1.8	2.7	-	V
			T _j =175°C	-	1.90	-	V
I _{GSS}	Gate-Source Leakage Current	V _{GS} =15V, V _{DS} =0V, T _j =25°C	-	-	1000	nA	
R _{DS(on)} (Chip)	Static drain-source	I _D =400A V _{GS} =15V	T _j =25°C	-	5.2	7.5	mΩ
	On-state resistance		T _j =175°C	-	11.6	-	mΩ
V _{DS(on)} (Chip)	Static drain-source	I _D =400A V _{GS} =15V	T _j =25°C	-	2.08	3.0	V
	On-state Voltage		T _j =175°C	-	4.64	-	V
V _{SD}	Body Diode Forward Voltage	V _{GS} =0V I _{SD} =400A	T _j =25°C	-	4.8	-	V
			T _j =175°C	-	4.2	-	V
C _{iss}	Input Capacitance	V _D =1000V, V _{GS} =0V f =1MHz, Vac =25mV	-	30.5	-	nF	
C _{oss}	Output Capacitance		-	0.82	-	nF	
C _{rss}	Reverse transfer Capacitance		-	0.15	-	nF	
Q _G	Total gate charge	V _{DD} =1000V, I _D =300A, V _{GS} =-5/+15V	-	1022	-	nC	
R _{Gint}	Internal Gate Resistance	T _j =25°C	-	0.48	-	Ω	
t _{d(on)}	Turn-on delay time	V _{DD} =900V I _D =400A V _{GS} =+15/-4V R _{G(on)} =6.8Ω R _{G(off)} =6.8Ω Inductive load switching operation	T _j =25°C	-	165	-	ns
			T _j =150°C	-	129	-	
t _r	Rise time		T _j =25°C	-	123	-	ns
			T _j =150°C	-	93	-	
t _{d(off)}	Turn-off delay time		T _j =25°C	-	515	-	ns
			T _j =150°C	-	646	-	
t _f	Fall time		T _j =25°C	-	80	-	ns
			T _j =150°C	-	102	-	
E _{on}	Turn-on power dissipation		T _j =25°C	-	48.4	-	mJ
			T _j =150°C	-	40.7	-	
E _{off}	Turn-off power dissipation	T _j =25°C	-	46.1	-	mJ	
		T _j =150°C	-	49.6	-		
R _{th(j-c)}	FET Thermal Resistance	Junction to Case	-	0.058	-	K/W	
R _{th(c-f)}	Contact thermal Resistance	With thermal conductive grease, Note1	-	0.015	-	K/W	

Note1: Assumes Thermal Conductivity of grease is 0.9W/m·K and thickness is 50um.

SiC SBD Electrical characteristics ($T_j=25^\circ\text{C}$ unless otherwise specified, chip)

Symbol	Item	Condition	Value			Unit	
			Min.	Typ.	Max		
V_{RRM}	Repetitive Peak Reverse Voltage	$T_j=25^\circ\text{C}$	-	1700	-	V	
V_F	Forward Voltage	$I_F=400\text{A}$	$T_j=25^\circ\text{C}$	-	1.8	-	V
			$T_j=175^\circ\text{C}$	-	2.9	-	
I_{RRM}	Reverse Current	$V_{RRM}=1700\text{V}$	$T_j=25^\circ\text{C}$	-	8	200	uA
			$T_j=175^\circ\text{C}$	-	164	-	
Q_C	Total Capacitive Charge	$I_F \leq I_{F,MAX}$ $dI_F/dt = 200\text{A}/\mu\text{S}$	$V_R=600\text{V}$	-	1432	-	nC
			$V_R=1200\text{V}$	-	2096	-	
C	Total Capacitance	$f=1\text{MHz}$	$V_R=1\text{V}$	-	18308	-	pF
			$V_R=1200\text{V}$	-	1008	-	
T_{rr}	Reverse recovery time	$V_{RR}=600\text{V}, I_F=400\text{A}$ $V_{GS}=+15/-4\text{V}$ $R_G=6.8\Omega$ Inductive load	$T_j=25^\circ\text{C}$	-	19	-	ns
			$T_j=150^\circ\text{C}$	-	17	-	
E_{rr}	Diode switching power dissipation	$R_G=6.8\Omega$ Inductive load	$T_j=25^\circ\text{C}$	-	0.81	-	mJ
			$T_j=150^\circ\text{C}$	-	1.08	-	
$R_{th(j-c)}$	SiC SBD Thermal Resistance	Junction to Case	-	0.063	-	K/W	
$R_{th(c-f)}$	Contact thermal Resistance	With thermal conductive grease, Note1	-	0.015	-	K/W	

Note1: Assumes Thermal Conductivity of grease is $2.8\text{W}/\text{m}\cdot\text{K}$ and thickness is $50\mu\text{m}$.

Test Conditions




Figure 3. Switching time measure circuit






Figure 4. Switching time definition






Figure 7. I_F vs V_F
 T_j parameter




Figure 8. $R_{DS(ON)}$ vs T_j
 $V_{GS} = +15\text{V}$, $I_D = 400\text{A}$, $1.0X = 5.2\text{m}\Omega$




Figure 9. $R_{DS(ON)}$ vs I_{DS}
 $T_j = 25^\circ\text{C}$, $V_{GS} = +15\text{V}$, $1.0X = 5.2\text{m}\Omega$




Figure 10. V_{GS} vs Q_g
 $T_j = 25^\circ\text{C}$, $V_{DS} = 1000\text{V}$, $I_D = 300\text{A}$




Figure 11. $V_{GS(TH)}$ vs T_j
 $V_{GS}=V_{DS}$, $I_D=240mA$




Figure 12. E_{on} , E_{off} , E_{rr} vs R_g
 $T_j=25^\circ C$, $V_{CC}=900V$, $V_{GS}=+15V/-4V$, $I_D=400A$
 Inductive Load




Figure 13. E_{on} , E_{off} , E_{rr} vs R_g
 $T_j=150^\circ C$, $V_{CC}=900V$, $V_{GS}=+15V/-4V$, $I_D=400A$
 Inductive Load






Figure 14. E_{on} , E_{off} , E_{rr} vs I_D
 $T_j=25^\circ C$, $V_{CC}=900V$, $V_{GS}=+15V/-4V$, $R_g=6.8\Omega$
 Inductive Load



Package dimensions



IMPORTANT NOTICE:

This product data sheet describes the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively under the terms and conditions of the supply agreement. There will be no guarantee or of any kind for the product and its characteristics.

The data contained in this document is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the product's suitability for the intended application and the completeness of the product data concerning such application.

Due to technical requirements, our product may contain dangerous substances. For information on the types in question, please contact the sales staff responsible for you.

Changes to this product data sheet are reserved.

Please contact the sales staff (Sales@leapers-power.com) for further information on the product, technology, delivery terms, conditions and prices.